

Standard Resolution Colour IR Dome Camera

TANDÉR® VDM24IR-K

KEY FEATURES

- 1/3" SONY SUPER HAD CCD
- 420 TV LINES
- 0.1 LUX (CDS SENSOR ON 0.00 LUX)
- BUILT IN 24 IR LED
- WATER PROOF & VANDAL PROOF



SPECIFICATION

| DESCRIPTION | VDM24IR-K | |
|-------------------------|---|--------------------------|
| Image Sensor | 1/3" Sony Super HAD CCD Sensor | |
| Effective Pixels | NTSC=510(H) * 492(V) | PAL=500(H) * 582(V) |
| Scanning System | 2:1 Interlaced | |
| Sync System | Internal Sync | |
| Resolution | 420 TV Lines | |
| Usable Illumination | 0.1 Lux (CDS Sensor on 0.00 Lux) | |
| S/N Ratio | More than 45dB | |
| Video Output | Composite Video Signal : 1.0Vp-p 75 ohm | |
| Electronic Shutter Time | NTSC=1/60 ~ 1/100,000 Sec | PAL=1/50 ~ 1/100,000 Sec |
| Power Supply | DC 12V | |
| Power Consumption | 350mA | |
| Lens | 4 / 6 mm Fixed Lens | |
| Operating Temperature | -10°C ~ +50 °C RH95% Max | |
| Storage Temperature | -21 °C ~ +60 °C RH95% Max | |
| Dimension | Ø 97(W)mm x 80(D)mm | |
| Country of Origin | Korea | |

Dimensions

(UNIT: mm)

